


<b>MATERIAL SAFETY Data Sheet</b>	EMERGENCY PHONE NUMBER	HAZARD RATING 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT **SEE SECTION V	
	800.346.9090		

### I. General Information

Manufacturer <b>ULTRASEAL INTERNATIONAL, INC.</b> <b>1100 N. WILCOX AVENUE</b> <b>LOS ANGELES, CA 90038</b>	TRADE NAMES & SYNONYMS <b>ULTRASEAL TIRE SEALANT – P/N's 7511/7150/7110 and 7110T</b>		
DOT Hazard Classification	<b>NOT HAZARDOUS</b>	Chemical family	<b>MIXTURE</b>
Proper DOT Shipping Name <b>COMPOUND, FLUID, NOIBN</b>			
Prepared By: <b>D.C. ATKINS &amp; SON, INC.</b> Date: <b>January 1, 2012</b>	<b>LEGEND:</b> N/E = Not Established N/A = Not Applicable		

### II. Ingredients

Hazardous Components	CAS Number	Percent	ACGTH TLV
<b>ETHYLENE GLYCOL</b>	<b>107-21-1</b>	<b>&lt;30</b>	<b>50 ppm</b>

### III. Physical Data

Boiling Point (deg. F): <b>121-127°C, (250-260°F)</b>	Specific Gravity (H2O=1): <b>1.08</b>
Vapor Pressure ( mm Hg @ 20°C (68°F): <b>&lt;20 mmHg</b>	Percent Volatile: <b>92</b>
Vapor Density (Air=1): <b>1.3</b>	Evaporation Rate (water=1): <b>Approximately 1.0</b>
Solubility in Water: <b>Approximately 90% soluble</b>	Reactivity in Water: <b>NONE</b>
Appearance & Odor: <b>VISCOUS FIBER SUSPENSION, MILD ODOR</b>	pH: <b>8.5-9.0</b>

### IV. Fire & Explosion Hazard Data

Flash Point (Test Method) SetaFlash Closed Tester <b>NONE</b>	Flammable Limits UEL <b>NE</b> LEL <b>NE</b>
	Auto Ignition Temperature <b>NE</b>
Extinguishing Media <input checked="" type="checkbox"/> Foam <input type="checkbox"/> Alcohol Foam <input checked="" type="checkbox"/> CO2 <input type="checkbox"/> Dry Chemical <input checked="" type="checkbox"/> Water Spray <input checked="" type="checkbox"/> Water <input type="checkbox"/> Not Applicable <input type="checkbox"/> Other	
Special Fire Fighting Procedures: <b>NONE</b>	
Unusual Fire & Explosion Hazards: <b>NONE</b>	

<b>V. Health Hazard Data</b>		
Threshold Limit Value of Product	<b>OSHA TEV</b>	<b>ACGTH TLV</b> See section II
		Carcinogen <b>NONE</b>
<b>SYMPTOMS OF EXPOSURE AND ROUTES OF</b>		
EYES: IRRITATION		
SKIN: POSSIBLE IRRITATION ON PROLONGED CONTACT		
INHALATION: IRRITATION TO RESPIRATORY TRACT		
INGESTION: IRRITATION TO THE GASTROINTESTINAL TRACT		
<b>FIRST-AID MEASURES</b>		
EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS		
SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND FOOTWEAR		
INHALATION: REMOVE TO FRESH AIR		
INGESTION: GIVE TWO GLASSES OF WATER. INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY		
<b>VI. Reactivity Data</b>		
Stability	<input type="checkbox"/> Unstable <input checked="" type="checkbox"/> Stable	Conditions to Avoid
Incompatibility		Materials to Avoid NONE
Hazardous Polymerization	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	Conditions to Avoid N/A
Hazardous Decomposition Products		
<b>OXIDES OF CARBON ON INCINERATION</b>		
<b>VII. Environmental Protection Procedures</b>		
Spill Response		
<b>SMALL SPILL:</b> WIPE UP		
<b>LARGE SPILL:</b> DIKE AREA. PUMP INTO TANK FOR RECOVERY OR DISPOSAL		
Waste Disposal Method		
INCINERATE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS		
<b>VIII. Special Protection Information</b>		
Eye Protection <b>NOT NORMALLY NEEDED</b>	Skin Protection <b>NOT NORMALLY NEEDED</b>	
Respiratory Protection (specific type) <b>NOT NORMALLY NEEDED</b>	Ventilation Recommended <b>GENERAL</b>	
Other Protection <b>MATERIAL IS SLIPPERY</b>		
<b>IX. Special Precautions</b>		
Hygienic Practices in Handling & Storage <b>STORE IN DOORS</b>		
Other Precautions <b>KEEP CLOSURES ON CONTAINERS WHEN NOT IN USE</b>		
Disposal of Empty Containers	<b>FLUSH WITH WATER BEFORE DISPERSING.</b>	<b>SHELF LIFE IS 5 YEARS</b>